


# FSWL2UCWH

Base Product



TeraSPEED® LC/UPC Keyed Yellow to Unconnectorized, Distribution Cable, 48-Fiber, Plenum

## Product Classification

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Regional Availability | North America                                                     |
| Portfolio             | CommScope®                                                        |
| Product Type          | Fiber distribution cable assembly                                 |
| Product Brand         | SYSTIMAX InstaPATCH® 360                                          |
| Ordering Note         | For lengths greater than 999 ft (304 m), orders must be in meters |

## General Specifications

|                                |                      |
|--------------------------------|----------------------|
| Cable Glands                   | No glands            |
| Color, connector A             | Yellow               |
| Construction Type              | Distribution, indoor |
| Interface, Connector A         | LC/UPC               |
| Interface Feature, connector A | Keyed                |
| Interface, Connector B         | Unterminated         |
| Total Fibers, quantity         | 48                   |

## Dimensions

|                                  |         |
|----------------------------------|---------|
| Cable Assembly Length Range (m)  | 1 – 61  |
| Cable Assembly Length Range (ft) | 1 – 200 |

## Mechanical Specifications

|                                   |                                |
|-----------------------------------|--------------------------------|
| Cable Retention Strength, maximum | 0.50 lb @ 0 °   0.50 lb @ 90 ° |
|-----------------------------------|--------------------------------|

## Optical Specifications

|            |                                |
|------------|--------------------------------|
| Fiber Mode | Singlemode                     |
| Fiber Type | G.652.D   G.657.A1, TeraSPEED® |

# FSWL2UCWH

## Environmental Specifications

|                       |                                      |
|-----------------------|--------------------------------------|
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Environmental Space   | Indoor   Plenum                      |

## Regulatory Compliance/Certifications

|               |                                                                                |
|---------------|--------------------------------------------------------------------------------|
| Agency        | Classification                                                                 |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |

## Included Products

|                 |   |                                                                                                                                                                |
|-----------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 760102921       | – | TeraSPEED® Behind The Wall Keyed LC Connector for 0.9 mm Fiber, Singlemode, yellow                                                                             |
| SFC-LCR-09-KYL  |   |                                                                                                                                                                |
| P-048-DS-8W-FMU | – | Fiber indoor cable, TeraSPEED® Plenum Distribution, 48 fiber multi-unit with 12 fiber subunits, Singlemode G.652.D and G.657.A1, Gel-free, Feet jacket marking |