

# NGFB-TB1MLU



Next Generation Frame (NGF) Fiber Termination Block with IFC cable, 144 SC/UPC to Stub tail, singlemode, left oriented, upward cable exit, black, 31 meters

## Product Classification

|                       |                                      |
|-----------------------|--------------------------------------|
| Regional Availability | EMEA   Latin America   North America |
| Product Type          | Fiber patch block, with IFC cable    |
| Product Series        | NGFB                                 |

## General Specifications

|                       |                               |
|-----------------------|-------------------------------|
| Functionality         | Patching                      |
| Application           | Used in NGF-style frames only |
| Body Style            | Left orientation              |
| Cable Exit Location   | Upward                        |
| Color                 | Black                         |
| Color, front          | Black                         |
| Door Type, front      | Compression latch   Hinged    |
| Growth Configuration  | Fully loaded                  |
| Interface, front      | Unloaded                      |
| Interface, rear       | Stub tail                     |
| Rack Type             | NGF                           |
| Shelf Movement        | Fixed                         |
| Total Ports, quantity | 144                           |

## Material Specifications

|               |               |
|---------------|---------------|
| Finish        | Powder coated |
| Material Type | Steel         |

## Optical Specifications

# NGFB-TB1MLU

|                   |            |
|-------------------|------------|
| <b>Fiber Mode</b> | Singlemode |
|-------------------|------------|

## Environmental Specifications

|                                |                                      |
|--------------------------------|--------------------------------------|
| <b>Operating Temperature</b>   | -5 °C to +50 °C (+23 °F to +122 °F)  |
| <b>Storage Temperature</b>     | -40 °C to +70 °C (-40 °F to +158 °F) |
| <b>Relative Humidity</b>       | Up to 80%, non-condensing            |
| <b>Qualification Standards</b> | Telcordia GR-449-CORE                |

## Packaging and Weights

|                           |   |
|---------------------------|---|
| <b>Packaging quantity</b> | 1 |
|---------------------------|---|

## Regulatory Compliance/Certifications

| Agency     | Classification                                                                                                                 |
|------------|--------------------------------------------------------------------------------------------------------------------------------|
| CHINA-ROHS | Above maximum concentration value                                                                                              |
| REACH-SVHC | Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a> |
| ROHS       | Compliant/Exempted                                                                                                             |
| UK-ROHS    | Compliant/Exempted                                                                                                             |

